Split System Cooling
Single Phase – 1½-5 Tons



XL19i

Table SC-1-A — XL19i R-22 Split System Cooling — Single Phase with ComfortLink™ II

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.) H	W	D	Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size OD Gas	OD Liq.
2TTZ9030C1000A	200/230/1/60	30,000	50	37	34	445	72	18	30	7/8	3/8
2TTZ9036C1000A	200/230/1/60	36,000	50	37	34	442	74	22	35	7/8	3/8
2TTZ9048C1000A	200/230/1/60	48,000	50	37	34	454	74	25	40	1 1/8	3/8
2TTZ9060C1000A	200/230/1/60	60,000	50	37	34	459	73	37	60	1 1/8	3/8

Note: Because of limited capabilities, please refer to product data for approved combinations.



XL16i

Table SC-1-B — XL16i R-410A Split System Cooling — Single Phase

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.) H	W	D	Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size OD Gas	OD Liq.
4TTX6024B1000A	230/1/60	24,000	44	33	30	256	73	13	20	5/8	5/16
4TTX6036B1000A	230/1/60	36,000	42	37	34	287	72	24	40	3/4	3/8
4TTX6048B1000A	230/1/60	48,000	50	37	34	310	74	28	45	7/8	3/8
4TTX6060B1000A	230/1/60	60,000	50	37	34	355	74	35	60	7/8	3/8



XL15i

Table SC-1-C — XL15i R-22 Split System Cooling — Single Phase

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.) H	W	D	Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size OD Gas	OD Liq.
2TTX5024A1000A	208/230/1/60	24,000	46	37	34	283	72	14	20	3/4	5/16
2TTX5030A1000A	208/230/1/60	30,000	46	37	34	284	74	16	25	3/4	5/16
2TTX5036A1000A	208/230/1/60	36,000	50	37	34	300	72	18	30	7/8	3/8
2TTX5042A1000A	208/230/1/60	42,000	50	37	34	307	73	23	35	7/8	3/8
2TTX5048A1000B	208/230/1/60	48,000	50	37	34	337	72	24	40	1 1/8	3/8

PHASE OUT



XL15i

Table SC-1-D — XL15i R-410A Split System Cooling — Single Phase

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.) H	W	D	Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size OD Gas	OD Liq.
4TTX5018A1000A	200/230/1/60	18,000	42	37	34	271	73	11	15	1/2	3/8
4TTX5024A1000A	200/230/1/60	24,000	42	37	34	275	74	14	20	5/8	3/8
4TTX5030A1000A	200/230/1/60	30,000	42	37	34	276	73	17	25	3/4	3/8
4TTX5036A1000A	208/230/1/60	36,000	50	37	34	302	72	22	35	3/4	3/8
4TTX5042A1000A	208/230/1/60	42,000	50	37	34	305	73	28	45	3/4	3/8
4TTX5048A1000A	208/230/1/60	48,000	54	37	34	352	73	30	50	7/8	3/8
4TTX5060A1000A	208/230/1/60	60,000	54	37	34	354	74	36	60	1 1/8	3/8

* Information subject to change. Please confirm with current Product Data/Service Facts for current factory production.
** Rated in accordance with ARI Standard 270, section 5.3.6.

Ref: 4/29/08 3:21 pm

For complete equipment / combination selections and installation instructions, please refer to Product Data and/or Installers Guides.

Effective 4/28/08